



Three Piece Design Screwed Ball Valve, Full Bore

SUPER DUPLEX 5A / 2000/1500PSI

Fig No: V-255FST

Full Bore 1/4" ~ 2" (DN8 ~ DN50)



Features :

- Investment Casting Component
- Blow Out Proof Stem, Non Anti-Static Device
- ISO 5211 Mounting Flange Design
- In-line Maintenance
- Standard Stock Without Fire Safe Standard Sealing Kits (changeable)
- * Option : API 607 4th Edition Fire Safe Approved
- Sealing Kits can be changed upon request

Standard Compliance :

- Body Wall Thickness : EN 12516-1/2/3, ANSI B16.34
- Threaded End : BS 21 (BSP)
- BSPT
- ISO 228-1G
- DIN 2999
- ISO 7-1Rp
- Face to Face : MD's Standard
- Pressure Testing : API 598 / EN 12266

Specification :

- Working Pressure : 140 Bar (CWP) / 2000 PSI for DN8 ~ DN25
- 100 Bar (CWP) / 1500 PSI for DN32 ~ DN50
- Temperature : -20 to 180 °C (-4 to 356 °F) for RTFE.
- Suggested Application : Sea Water, Organic Acids, Caustic Soda, Phosphoric Acid

MATERIAL LIST

NO.	PART NAME	MATERIAL
1	BODY	ASTM A890/995 Gr.5A CE3MN
4	BALL	ASTM A890/995 Gr.5A CE3MN
5	STEM	S32750
9	END CAP	ASTM A890/995 Gr.5A CE3MN
11	BODY SEAL	PTFE.
12	SEAT	RTFE.(15%G.F.)
13	THRUST WASHER	PTFE.
14	STEM PACKING	PTFE.
15	GLAND BUSH	SS304
19	HANDLE	SS304
21	HANDLE COVER	PLASTIC
22	STEM NUT	SS304
24	HANDLE NUT	SS304
28	LOCKING PAD	SS304
29	BELLEVILLE WASHER	SS301
30	TAB WASHER	SS304
33	STOP PIN	SS304
34	STOP PIN NUT	SS304
35	BODY BOLT	ASTM A193 Gr.B8M
37	BOLT NUT	ASTM A194 Gr.8M

DIMENSIONS

SIZE	PORT	L	L3	E	H	H1	H2	h	W	ØK	C	ØD	ØY	Z	unit:mm
DN8	1/4"	10.0	64.8	16.0	132.8	62.7	8.6	6.7	0.5	29.5	36.0	6.5	25.0	9.5	M5x0.8
DN10	3/8"	10.0	64.8	16.0	132.8	62.7	8.6	6.7	0.5	29.5	36.0	6.5	25.0	9.5	M5x0.8
DN15	1/2"	15.0	72.5	16.75	132.8	69.0	16.5	8.0	2.0	30.0	36.0	6.5	25.0	9.5	M5x0.8
DN20	3/4"	20.0	85.4	18.0	132.8	73.5	17.8	8.8	2.0	36.0	36.0	6.5	25.0	9.5	M5x0.8
DN25	1"	25.4	105.3	21.0	171.8	81.9	25.3	12.0	2.0	44.5	42.0	8.0	30.0	11.1	M5x0.8
DN32	1-1/4"	32.0	111.0	22.0	171.8	86.9	26.0	11.7	2.0	54.0	42.0	8.0	30.0	11.1	M5x0.8
DN40	1-1/2"	38.0	127.3	25.0	204.2	97.5	31.7	15.0	2.2	60.0	50.0	9.7	35.0	14.2	M6x1.0
DN50	2"	50.8	145.2	27.2	212.0	127.0	28.7	15.4	1.8	73.0	70.0	12.0	55.0	19.0	M8x1.25

DIMENSIONS

SIZE	PORT	L	L3	E	H	H1	H2	h	W	ØK	C	ØD	ØY	Z	unit:inch
DN8	1/4"	0.39	2.55	0.63	5.23	2.47	0.34	0.26	0.02	1.16	1.42	0.26	0.98	0.37	M5x0.8
DN10	3/8"	0.39	2.55	0.63	5.23	2.47	0.34	0.26	0.02	1.16	1.42	0.26	0.98	0.37	M5x0.8
DN15	1/2"	0.59	2.85	0.66	5.23	2.72	0.65	0.31	0.08	1.18	1.42	0.26	0.98	0.37	M5x0.8
DN20	3/4"	0.79	3.36	0.71	5.23	2.89	0.70	0.35	0.08	1.42	1.42	0.26	0.98	0.37	M5x0.8
DN25	1"	1.00	4.15	0.83	6.76	3.22	1.00	0.47	0.08	1.75	1.65	0.31	1.18	0.44	M5x0.8
DN32	1-1/4"	1.26	4.37	0.87	6.76	3.42	1.02	0.46	0.08	2.13	1.65	0.31	1.18	0.44	M5x0.8
DN40	1-1/2"	1.50	5.01	0.98	8.04	3.84	1.25	0.59	0.09	2.36	1.97	0.38	1.38	0.56	M6x1.0
DN50	2"	2.00	5.72	1.07	8.35	5.00	1.13	0.61	0.07	2.87	2.76	0.47	2.17	0.75	M8x1.25

